



Super Vac and Mobile Super Vac

KSW Oilfield Rental
Corporate Office:
6931 S. 66th E. Ave.
Suite 105
Tulsa, OK 74113
918.933.6857

www.dupre.com/kswoilfield

Key Features

- Able to vacuum-up wet or dry material (oil or water based mud, diesel, antifreeze, chemical spills, etc.)
- Large 35 BBL capacity
- Manifold – 5 valve for easy operation
- Explosion proof control panel
- Conical shape for easy discharge / cleanout
- Manway on top and bottom
- Removable skid for ease of changing pump / electric motor
- Empty weight 4,500 lbs.
- Direct drive pump and motor
- Eliminates the use of belts (no down time on changing broken belts)
- Indicator light aluminates while in operation for added safety
- Low oil switch – shuts off pump and motor to prevent damage to pump
- Overfill cut off switch – eliminates overfilling of the vac (no down time and service calls)

Vacuum Pump

- RPM range 900 - 1200
- Max vacuum 27.6" - 92%
- Max continuous vacuum 18" - 60%
- CFM at free air 363
- CFM at 18" 304
- Max intermittent pressure 21 PSI
- Horsepower 20
- Noise level at 18" - 60% 84 db(A)
- Oil tank capacity 15 gal
- Net weight 397 lbs.
- Recommended oil ISO 150
- 1 3/8" Smooth shaft
- 2 - 3" Swivel elbows





Super Vac and Mobile Super Vac

KSW Oilfield Rental
Corporate Office:
6931 S. 66th E. Ave.
Suite 205
Tulsa, OK 74113
918.933.6857

www.dupre.com/kswoilfield

Filtration

- Filtration cartridge for wet or dry application
- Washable, reusable final filter
- 10 gallon secondary shut off w/ deflection chute and stainless steel float ball

Motor

- 20 HP Marathon Model 256TTGN1026
- Explosion Proof
- RPM 1800
- 480 volt
- 3 phase
- weight 410 lbs.

Control Panels

- Explosion proof, water proof, and lockable
- Manual and auto switch
- Vacuum / PSI gauge
- Pressure switch to automatically shut off pump at max PSI or vacuum
- Explosion proof CGB fittings

Collection Tank

- 35 Barrel capacity
- 20" Full opening top and bottom hatch
- 4" Discharge

